

Pneumatic Sanding Sets

SNT-202 Series



SNT Series Control Panel

- Dust Extractor
MAN Running
- Dust Extractor
Replace brush
- Dust Extractor
Run 000 H 01Min
- Dust Extractor
AUTO Running
- Dust Extractor
Dust out

- High Brightness Indicator
- Eye Protection Without Splash Screen
- Stable Performance
- Continuous Operation

Efficiency

Intelligence

Technology

Environment

Features:



Streamlined shape, with national appearance patent.



Intelligent automatic control unit, steady performance, safe and reliable.



Strong extraction power, less dust pollution.



Imported professional vacuum motor, stable and durable.

Technical data: (Standard Configuration)

Voltage/Frequency	220V/50Hz
Power consumption	350-1200W
Noise	≤ 70dB
Vacuum	≥ 28000Pa
Operation Pressure	≥ 0.7MPa
Rubber-insulated mains cable	5m
Appliance socket connected load	≤ 600W
Container capacity	36L
Max. volume flow	3900L/min
Weight	54kg
Filter surface area	6800cm ²
Shape Size (mm)	610×710×1310mm (L × W × H)
Packing Size (mm)	730×620×1050mm (L × W × H)
★ Electric Orbit Sander is optional	

Note: if there is inconsistency between the image and actual product, the actual product shall govern.

◆ Apply to automobile repair & maintenance, auto fast repair and beauty chains, car 4S shops, automobile, train, ship, woodworking manufacturing enterprises, and the outer surface treatment of parts in various industries.

Add: A10, 2F, Building 4, No.206, West 4th Ring Rd,
 HI-NEW Tech Zone, Zhengzhou, Henan, P.R.China
 TEL: +86 371-67575169
 FAX: +86 371-67575168
 Website: www.sinotint.com